

PPD 2500

OPTIONAL



- Pad cleaning attachment
- Servo-Motor drive pad stroke
- Servo-Motor drive carriage stroke
- Dwell function valve for texture surface printing



- Side way ink cup for long image printing (SCMIC)



- DPS multi-color pad shuttle attachment



- Pneumatic shuttle attachment



- Different size conveyor



- Digital shuttle attachment

FEATURES

- A versatile single or multi color pad printer
- Pneumatic power or fully digital Servo-Motor drive
- Use Ceramic ink cup (CMIC) or open ink tray
- Use long life thin steel, polymer and 10 mm printing plate
- 0 - adjustment, Dead-on printing plate registration
- Microprocessor, membrane control panel
- Emergency power shut off, sliding side door
- Automatic pad stroke (APS) for variable printing depth
- CNC machine aluminum plate machine frame
- Hardened, precision ground steel shaft with impregnated bushing ensures friction-free movement
- High speed, smooth machine movement
- Easily converted to 2, 3, 4, 5 or 6 color setup
- Able to use all Kent automation accessories

SPECIFICATIONS

Max. ink cup:	Ø90, 130, 150 mm
Max. plate size:	100/180 x 250 mm - 350 mm
Carriage stroke:	350 mm
Max. no. of cups:	Ø90 x 6
Power:	110/220V 50/60Hz 50W
Air consumption:	500 Litre / Min.
Speed: (depend on pad Ø):	720/hr.
Measurement:	1200 x 676 x 1821 mm
Weight:	650 Kg (Approx.)