

# TURBO 350

## Economic Version



TÜVRheinland®  
**CERT**  
ISO 9001  
ISO 14001

Exclusive US Agent of:  
**KENT**  
INTERNATIONAL



PLC and touch screen panel



2 Independent pad cylinders



Turbo pad clean feature



Pad in/out stroke for max. throat depth



Precision servo product shuttle (DRE)

### FEATURES

- Turbo pad clean design for 2 color printing
- Rigid steel machine structure
- Both pad & printing plate platform in/out design for max. product size
- Two independent pad cylinders
- Pneumatic pad in/out carriage
- Servo drive product shuttle attachment
- Two Green ink cups (125mm)
- Able to use laser engraved Green plate, thin steel plate or polymer printing plates
- Dead-on printing plate registration for quick job change
- PLC control with large touch screen panel
- Programmable pad stroke and speed adjustment
- Programmable pad clean cycle
- Adjustable dwell and delay time
- Complete cabinet with light beam curtain (Optional)

### SPECIFICATIONS

<b>Ink cup:</b>	Ø125 mm x 2
<b>Printing plate size:</b>	150 x 350 mm
<b>Max. speed:</b> (dry cycle)	700 / hr. (2 color)
<b>Pad cylinder:</b>	Ø50 x 125 mm x 2
<b>Pad carriage stroke in/out:</b>	250 mm
<b>Power:</b>	110/220V
<b>Air consumption:</b>	390 liter/min. (approx.)
<b>Accuracy +/-:</b>	0.025 mm
<b>Size:</b> (L x W x H)	850 x 500 x 1,500 mm
<b>Weight:</b>	370 kg (approx.)