

TURBO 350

Economic Version



TÜVRheinland®
CERT
ISO 9001
ISO 14001

Exclusive US Agent of:
KENT
INTERNATIONAL



PLC and touch screen panel



2 Independent pad cylinders



Turbo pad clean feature



Pad in/out stroke for max. throat depth



Precision servo product shuttle (DRE)

FEATURES

- Turbo pad clean design for 2 color printing
- Rigid steel machine structure
- Both pad & printing plate platform in/out design for max. product size
- Two independent pad cylinders
- Pneumatic pad in/out carriage
- Servo drive product shuttle attachment
- Two Green ink cups (125mm)
- Able to use laser engraved Green plate, thin steel plate or polymer printing plates
- Dead-on printing plate registration for quick job change
- PLC control with large touch screen panel
- Programmable pad stroke and speed adjustment
- Programmable pad clean cycle
- Adjustable dwell and delay time
- Complete cabinet with light beam curtain (Optional)

SPECIFICATIONS

Ink cup:	Ø125 mm x 2
Printing plate size:	150 x 350 mm
Max. speed: (dry cycle)	700 / hr. (2 color)
Pad cylinder:	Ø50 x 125 mm x 2
Pad carriage stroke in/out:	250 mm
Power:	110/220V
Air consumption:	390 liter/min. (approx.)
Accuracy +/-:	0.025 mm
Size: (L x W x H)	850 x 500 x 1,500 mm
Weight:	370 kg (approx.)