

PP150



OPTIONAL

Pad cleaning attachment (optional)
Machine stand (optional)



Different size conveyors (2 - 5 color)



Pneumatic shuttle (2 - 4 color)



Digital shuttle for multi-color



DPS multi-color pad shuttle attachment



Side way ink cup for long image printing (SCMIC)

FEATURES

- Microprocessor control, pneumatic operated pad printer
- Use open ink tray or ceramic ink cup (CMIC)
- Use long life thin steel, polymer or 10 mm steel plate
- 0 - adjustment dead on printing plate registration for fast job change
- Membrane switch control panel
- Preprogrammed with 44 stored print options (special program on request)
- Dwell function valve for texture surface printing
- Variable pad delay prior to printing to maximize ink transfer
- Emergency power shut-off (optional)
- Light weight, rigid aluminum cast machine frame
- Hardened, precision ground shaft with oil-impregnated bushing gives friction-free machine movement
- Independent pad stroke & speed adjustment
- APS : Automatic pad stroke
- Easily converted to 2, 3, 4 or 5 color machine with shuttle attachment or carousel conveyor

SPECIFICATIONS

Ink cup size :	Ø 60, 70, 90 and 130 mm
Plate for ink cup size :	80 x 250mm, 100 x 250mm, 150 x 300mm
Plate for ink tray size :	100 x 100 → 450 mm, 150 x 100 → 450 mm
Max. print diameter :	125 mm
Max. print length :	400 mm
Max. speed : <small>(no automation attach)</small>	1,300 cycles/hr.
Max. pad pressure :	1,800N at 6 bar
Power :	110/220V 60/50Hz 50W
Air consumption :	228 litre/min. (approx.)
Size : L x W x H	1,000 x 592 x 1,630 mm
Weight :	150 kg (approx.)